

17.0000 in

**GREEN SEAL™ CERTIFIED, HIGH SOLIDS FLOOR FINISH AND SEALER. PROTECTS AND BEAUTIFIES ALL FLOORS. HIGH GLOSS FLOOR FINISH APPLIES EASILY, DRIES QUICKLY TO A HIGH GLOSS AND REPAIRS EASILY. IT'S FOR USE WITH ALL MAINTENANCE SYSTEMS, INCLUDING NO-BUFF, SPRAY BUFF AND HIGH SPEED BURNISHING. LOW ODOR FORMULA MAKES IT THE PERFECT CHOICE**



**NATURALLY TOUGH**



**Ammonia-free, Zinc-free  
Phthalate-free, APEO-free  
Butyl-free, Caustic-free**

**Great For:**

Hospitals · Schools · Retailers · Hotels  
Restaurants · Residential · Industrial Facilities  
and Fire & Water Damage/Restoration



**BIOESQUE®**

# HIGH GLOSS FLOOR FINISH

**HEAVY DUTY · PROTECTS**



COMBINATION SEAL AND FINISH



NON-YELLOWING,  
LOW MAINTENANCE  
FORMULA



AMMONIA  
FREE

**Directions For Use:**

**Application:**

1. Strip to remove old waxes, sealers and finishes.
2. Rinse thoroughly and let dry.
3. With clean finish mop apply thin, even coats of High Gloss Floor Finish using figure 8 motions overlapping the strokes.
4. Under normal conditions, allow to dry for 20 minutes between coats.
5. For best results, apply a maximum of 4 coats in 24 hours.
6. Allow 48 hours for the finish to reach full cure before wet cleaning. Burnishing will speed cure time.

**Maintenance:**

**Daily:**

1. Sweep or dust mop as necessary to remove gritty soil.
2. Use Bioesque Neutral Floor Cleaner to damp mop spills as they occur. Damp mop or auto-scrub nightly with Bioesque Neutral Floor Cleaner.
3. **Buffing:** If desired, periodic burnishing with semi-soft blended pads will enhance

appearance and shine.

**Weekly:**

1. To repair and deep clean floor, apply a green restorer with mop or auto-scrubber.
2. Allow floor to dry.
3. Burnish floor with high speed equipment. This finish also responds to spray buffing with conventional speed equipment.

**Note:** Always dust mop after burnishing or spray buffing.

**Periodic Recoating:**

1. Dust mop entire floor then scrub aggressively using a restorer and auto-scrubber with a red or green pad.
2. Rinse floor and allow to dry.
3. Apply Bioesque High Gloss Floor Finish

**Improper application:**

Over application of finish may cause floor to be tacky, streaked and/or ghosted looking, dull and prone to black marking and scuffing.

**STORAGE:** KEEP CONTAINER TIGHTLY CLOSED IN A COOL DRY AREA.  
**DISPOSAL:** DISPOSE OF IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS.

MADE IN USA

QUESTIONS? Talk to us.  
bioesquesolutions.com

Distributed by NatuReal, LLC  
2091 NE 36th Street #50548  
Lighthouse Point, FL 33074  
800.921.4634



**NON-FLAMMABLE AND NON-CORROSIVE FOR A SUPERIOR FINISH THAT IS FRIENDLIER TO THE ENVIRONMENT.**

**KEEP OUT OF REACH OF CHILDREN  
NET CONTENTS: 1 GALLON (3.78 L)**

**WARNING: KEEP OUT OF REACH OF CHILDREN.** READ LABEL BEFORE USE. IF MEDICAL ADVICE IS NEEDED, HAVE PRODUCT CONTAINER OR LABEL AT HAND. FIRST AID: CONTACT WITH EYES: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER, OCCASIONALLY LIFTING THE UPPER AND LOWER EYELIDS. CHECK FOR AND REMOVE ANY CONTACT LENSES. GET MEDICAL ATTENTION IF IRRITATION OCCURS. SKIN CONTACT: FLUSH CONTAMINATED SKIN WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INHALATION: REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. GET MEDICAL ATTENTION IF SYMPTOMS

OCCUR. **INGESTION:** WASH OUT MOUTH WITH WATER. REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. IF MATERIAL HAS BEEN SWALLOWED AND THE EXPOSED PERSON IS CONSCIOUS, GIVE SMALL QUANTITIES OF WATER TO DRINK. DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. **CONTAINS:** 122-99-6; ETHYLENE GLYCOL MONOPHENYL ETHER, 100-51-6; BENZYL ALCOHOL. **FOR MORE INGREDIENT INFORMATION VISIT:** WWW.BIOESQUESOLUTIONS.COM OR CALL 800-921-4634



8 18432 02007 3

6.0000 in